

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

B/ Claim 1 (currently amended). A lock for overlapping parallel sliding members, comprising:

a hinge member having two leaves;

the two leaves including a fixed leaf permanently secured to one of overlapping sliding members, and a pivotal leaf pivotally moveable between locked and unlocked positions, to permit sliding of said overlapping members in the unlocked position, and, when turned about 90 degrees to the locked position, to abut the face of one of said overlapping members to prevent displacement there between; and

a resistance mechanism for lightly-resisting pivoting of said pivotal leaf against displacement or rotation in the locked position, said resistance mechanism requiring no pre-manipulation of any portion of the lock prior to pivoting movement;

wherein the resistance mechanism provides for lightly-resisting pivoting of said pivotal leaf against displacement or rotation in both the locked and unlocked positions;

wherein said resistance mechanism comprises a cam on one of said leaves having at least one flattened lobe, the at least one flattened lobe corresponding to the locked position, and a displaceable follower on the other leaf engaged with the cam for providing light resistance to pivoting relative movement of the leaves when said follower is engaged with said flattened lobe;

wherein the follower has a planar surface engaged with the cam, the planar surface being

engageable with the at least one flattened lobe of cam when the pivotal leaf is in the locked position; and

wherein the follower is formed of a deformable material, and the follower is dimensioned to permit increased elastic deformation thereof by the cam during pivoting relative movement of the leaves.

Claims 2-11 (canceled).

B | Claim 12 (currently amended). The device of claim 3 1 with a central location located in abutting inner longitudinal edges of the leaves, and the cam and follower being located in the central location.

Claim 13 (canceled)

Claim 14 (previously presented). The device of claim 12 with the follower extending from a raised central portion of the pivotal leaf.

Claim 15 (canceled)

Claim 16 (currently amended). The device of claim 3 1 with the pivotal leaf having an outer longitudinal edge sloped outwardly away from a hinge axis of the leaves and a surface of the sliding member adjacent to pivotal leaf when the pivotal leaf is in the unlocked position.

Claim 17 (canceled)

Claim 18 (previously presented). A lock for overlapping parallel sliding members, comprising:

a hinge member having two leaves;

the two leaves including a fixed leaf permanently secured to one of overlapping sliding members, and a pivotal leaf pivotally moveable between locked and unlocked positions, to permit sliding of said overlapping members in the unlocked position, and, when turned about 90 degrees to the locked position, to abut the face of one of said overlapping members to prevent displacement there between;

a resistance mechanism for lightly-resisting pivoting of said pivotal leaf against displacement or rotation in the locked position, said resistance mechanism requiring no pre-manipulation of any portion of the lock prior to pivoting movement;

wherein said resistance mechanism comprises a cam on one of said leaves having at least one flattened lobe, the at least one flattened lobe corresponding to the locked position, and a displaceable follower on the other leaf engaged with the cam for providing light resistance to pivoting relative movement of the leaves when said follower is engaged with said flattened lobe;

wherein the follower has a planar surface engaged with the cam, the planar surface being engageable with the at least one flattened lobe of cam when the pivotal leaf is in the locked position;

wherein the cam is located on the fixed leaf and the follower is located on the pivotal leaf;

wherein the follower is formed of a deformable material, and the follower is dimensioned to permit increased elastic deformation thereof by the cam during pivoting relative movement of the leaves;

with the follower being non-deformed when the pivotal leaf is in the locked position;

with the cam and follower being centrally located in abutting inner longitudinal edges of the leaves;

with the follower extending from a raised central portion of the pivotal leaf; and

with the pivotal leaf having an outer longitudinal edge sloped outwardly away from a hinge axis of the leaves and a surface of the sliding member adjacent to pivotal leaf when the pivotal leaf is in the unlocked position.

Claim 19 (previously presented). A lock for overlapping parallel sliding members, comprising:

a hinge member having two leaves;

the two leaves including a fixed leaf permanently secured to one of overlapping sliding members, and a pivotal leaf pivotally moveable between locked and unlocked positions, to permit sliding of said overlapping members in the unlocked position, and, when turned about 90 degrees to the locked position, to abut the face of one of said overlapping members to prevent displacement there between;

a resistance mechanism for lightly-resisting pivoting of said pivotal leaf against displacement or rotation in the locked position, said resistance mechanism requiring no pre-manipulation of any portion of the lock prior to pivoting movement,

wherein the resistance mechanism provides for lightly-resisting pivoting of said pivotal leaf against displacement or rotation in both the locked and unlocked positions;

wherein said resistance mechanism comprises a cam on one of said leaves having at least two flattened lobes, at least one flattened lobe corresponding to the locked position and at least one other flattened lobe corresponding to the unlocked position, and a displaceable follower on the other leaf engaged with the cam for providing light resistance to pivoting relative movement of the leaves when said follower is engaged with either one of said flattened lobes;

B | wherein the cam is located on the fixed leaf and the follower is located on the pivotal leaf;

wherein the follower is formed of a deformable material, and the follower is dimensioned to permit increased elastic deformation thereof by the cam during pivoting relative movement of the leaves;

with the follower being non-deformed when the pivotal leaf is in the locked and unlocked position;

with the follower extending from a raised central portion of the pivotal leaf; and

with the pivotal leaf having an outer longitudinal edge sloped outwardly away from a hinge axis of the leaves and a surface of the sliding member adjacent to pivotal leaf when the pivotal leaf is in the unlocked position.